
TERRAFOR MODICK REFERENCE GUIDE

DEPTH

THRU

RATE



MIDI JACKS **IN/THRU**

> **EFFECT BLOCK SELECTOR**

STEREO/ MONO PRE/POST OUT

BYPASS STOMP

> PRESET **SWITCH**

effect RATE: effect DEPTH, output VARIABLE = waveform width

RTRY

PHAS

ENVE 6

STEREO RIGHT OUT

POST OUT

MONO LEET OUT

PRE OUT

A.WAH

FLNG

SWEL

DIME

TREM

CHOR

A HARM

AUTO SWELL

effect RATE; effect DEPTH; output VOLUME: clean BLEND: VARIABLE pick attack speed

ROTARY

speed/RATE; effect DEPTH; output max horn speed RATE; max woofer BLEND between horn/woofer, VARIABLE ramp speed.

U VIBE

PRESET / SAVE

VARIABLE

TERRAFORM 0000

> effect RATE; filter range DEPTH; output VOLUME; clean BLEND;

PHASER

effect RATE: DEPTH of filter range, VARIABLE stereo width, clean BLEND; output VOLUME

POWER INPUT

9v DC CENTER **NEGATIVE PIN ONLY**

EXPRESSION PEDAL INPUT

THE FIVE CONTROLS

HINT: THE BLEND IS **EVERYTHING FOR** FLANGER & PHASER

STEREO/MONO PRE/POST IN

TAP TEMPO **STOMP**

(ALSO TOGGLES RAMP FOR ROTARY)

VARIABLE waveshape

ENVELOPE FILTER

STEREO RIGHT IN

POST IN

MONO LEFT IN

attack speed/RATE; DEPTH envelope sensitivity; output VOLUME, clean BLEND; VARIABLE changes "Q"

effect RATE: effect DEPTH (max=TZF):

output VOLUME; clean BLEND; VARIABLE

AUTOWAH

FLANGER

feedback level

BLEND

VOLUME

autowah RATE; filter DEPTH; output VOLUME; clean BLEND, VARIABLE changes "Q"

DIMENSION

effect RATE; effect DEPTH; output VOLUME; clean BLEND; VARIABLE VOLUME; BLEND = stereo width, amount of bass


CHORUS

effect RATE: effect DEPTH: output VOLUME; clean BLEND; VARIABLE amount of bass

HARMONIC TREMOLO

VOLUME; BLEND = crossover point; speed DEPTH; output VOLUME, VARIABLE = width


TREMOLO



STEREO / MONO


FOR REGULAR STEREO / MONO USE SET TOP SWITCH TO NORMAL

(out left for mono - use the right output as well for stereo)



PRE / POST - STRAIGHT IN

FOR PRE / POST USE, STRAIGHT IN SET TOP SWITCH TO PRE/POST



PRE / POST - EFFECTS LOOP

FOR PRE / POST USE, WITH EFFECTS LOOP SET TOP SWITCH TO PRE/POST

PRESET - Set your tone, HOLD the PRESET button until it flashes, select the patch location with the PRESET button, and the hold it down again to store your tone in that location.

EXPRESSION - Hold down the bypass button and press TAP TEMPO, release both. Set the HEEL position of the control, press TAP TEMPO, set the TOE position of the control, press the TAP TEMPO stomp to exit.

PRE/POST - On power up, hold both the BYPASS and TAP TEMPO stomps and power up. Set each effect by selecting it and pressing BYPASS for pre (LED = green), or TAP TEMPO for post (LED = Blue), press the PRESET button to save your preferences.

POWER

This pedal was designed around the usage of a 9v power source. To avoid damage to the pedal, do NOT exceed 9vDC, do not use center pin positive adapters and do not use AC power. Using an incorrect power adapter can lead to damage and will void the warranty on the pedal.

This pedal draws approximately 130ma at 9v



FOR FURTHER DETAILS ON HOW TO UTILIZE THE ADVANCED FEATURES OF YOUR TERRAFORM VISIT: WWW.WAMPLERPEDALS.COM, VISIT THE DOWNLOAD SECTION AND GET THE FULL MANUAL